



HARSHPRO™ IP43 SERVER

Developed and manufactured in Singapore, the HarshPro IP43 Server is a powerful rugged server built for performance with an Intel® Xeon®¹ processor, multiple memory configurations, and high-capacity, high speed NVMe SSDs, enabling distributed cloud functionality and application containerization in a small footprint wherever you need it.

The server is housed in a compact enclosure designed for industrial environments that provides protection against dust and liquid while keeping overall equipment costs low. The HarshPro IP43 Server is equipped with a Trusted Platform Module to protect the security, integrity, and authenticity of the server.

HarshPro IP43 Server is designed to work standalone or clustered in remote locations. The server supports functionality commonly used in data centers including automated provisioning and remote management. The server offers three high speed M.2 slots and a single x16 PCIe slot for system expansion. The baseboard management controller (BMC) supports popular remote management technologies like IPMI, PXE, Redfish®, and KVM over IP which allows it to be fully administered remotely down to the BIOS level.



Photos for illustration purposes only, design not representative of IP43 rating.

¹ Intel and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries



HARSHPRO SMALL FORM FACTOR SERVER SPECIFICATIONS²

System Chipset

CPU:	Intel® Xeon® D - 1518	Intel® Xeon® D - 1539 ³
Maximum Speed:	2.2 GHz	1.6 GHz
Max Turbo Frequency:	2.2 GHz	2.2 GHz
L3 Cache:	6 MB	12 MB
Cores:	4	8
Threads:	8	16
BIOS:	AMI® APTIO-V® UEFI version 2.4 UEFI Platform Initialization version 1.3	
Motherboard	Micro ATX (mATX)	

Memory

Technology:	Dual channel 2133 MHz ECC 288 pin DDR4
Slots:	2 x DIMM Slots RDIMM (up to 32 GB per slot) UDIMM (up to 16 GB per slot)
Maximum Capacity:	64 GB (RDIMM)
ECC Support:	Yes

Baseboard Management Controller (BMC)

Chipset:	ASPEED AST2500
Firmware:	AMI® MegaRAC® SP-X
Protocols:	Redfish® 1.5, KVM over IP, IPMI 2.0

Trusted Platform Module (TPM) 2.0

TPM Module:	Infineon
Chipset:	OPTIGA™ TPM SLM 9670

² Specifications listed here may be subject to change

³ CPU Optional



Input/Output Interfaces

Ethernet Network Controllers:	1 GbE Intel®i210IT
Interfaces:	2 x 1000 Base-T Ethernet (BMC access through one port) 2 x USB2 4 x USB3.1

Display card

Display card:	ASUS NVIDIA GT 710 (sample)
Output:	4 x HDMI

Storage

Technology:	M.2 NVMe
Maximum Capacity:	Up to 6 TB (3 x 2 TB SSD)

Expansion Slots

M.2:	3 x M.2 M Key (2232/2240/2260/2280)
PCIe	1 x PCIe x16 physical (4 lanes)

LED and Switch

Button / LED:	Combined LED status & pushbutton
---------------	----------------------------------

Power

Input Voltage:	12V to 48V DC
Power Consumption:	TBC

Electrical Protection

Reverse polarity:	Yes
Over current:	Yes
Over voltage:	Yes



Environment⁴

Operating Temperature:	0°C to 40°C ⁵
Ambient Storage Temperature:	-40°C to 85°C
Humidity:	10-90% RH (operating and non-operating)
IP rating:	43
Cooling:	Forced convection

Mechanical⁶

	Base server	Server with IP43 kit
Dimensions:	150 mm H x 254 mm W x 264 mm D	150 mm H x 298 mm W x 350 mm D
Weight:	TBC	TBC
Installation:	Horizontal or Vertical	

OS Support:	CentOS v7.4 Red Hat® Enterprise Linux® (RHEL) v7.4/7.5/7.6 Red Hat® Enterprise Linux® (RHEL) Atomic v7.4 Ubuntu v18.04 Windows Server 2012 R2 Windows Server 2016 Windows 10 Pro
Certifications⁷:	EMC, FCC, CE, WEEE, UL, RoHS3, REACH

This datasheet is for information only. Products or corporate names may be trademarks or registered trademarks of other companies and are used only for the explanation and to the owners' benefit, without intent to infringe.

⁴ Subject to change

⁵ SFF operating temperature range is restricted by NVIDIA cards' operating temperature range

⁶ Subject to change

⁷ Subject to change